

County Surveyor's Record, Douglas County, Oregon

16398

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R 4 W., Willamette Meridian

CHAINS	
	<p>A cedar, 10 ins. diam., bears N. 44° E., 45 1/2 lks. dist., with healed blaze.</p> <p>A cedar, 8 ins. diam., bears S. 36° W., 26 lks. dist., with healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 46' W., beginning new measurement.</p> <p>Descend 15 ft. over SW slope.</p>
0.40	Creek, 3 lks. wide, course S.; asc. 75 ft. over SE slope.
7.30	Creek, 1 lk. wide, course S. 10° E.; asc. 5 ft. over SE slope.
7.70	Creek, 1 lk. wide, course S. 10° E.; asc. 165 ft. over SE slope.
20.40	Top of ascent, slopes S.; desc. 10 ft. over SW slope.
20.64	<p>The W 1/16 sec. cor. of secs. 9 and 16, established and recorded by Donald A. Bentz, Registered Land Surveyor, No. 839, in 1979, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by Bentz:</p> <p style="margin-left: 40px;">A cedar, 5 ins. diam., bears N. 51° E., 25 lks. dist., with scribe marks W 1/16 S9 BT visible on open blaze.</p> <p style="margin-left: 40px;">An oak, 13 ins. diam., bears S. 49° E., 11 1/2 lks. dist., with scribe marks W. 1/16 S16 BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} \text{W } 1/16 \frac{\text{S } 9}{\text{S } 16} \\ 1979 \end{array}$ </div> <p>from which a new bearing object</p> <p style="margin-left: 40px;">A basalt boulder, 15 x 12 x 8 ft. above ground, bears S. 13° E., 6 1/2 lks. dist., mkd. X BO on NW face.</p> <p style="margin-left: 40px;">Reset iron rod alongside iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>S. 89° 51' W., beginning new measurement.</p> <p>Descend 5 ft. over SW slope.</p>
1.80	Creek, 1 lk. wide, course S.; asc. 150 ft. over SE slope.
20.60	<p>The cor. of secs. 8, 9, 16, and 17, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p>