

County Surveyor's Record, Douglas County, Oregon

16299

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 24 S
S 8 | S 9
S 17 | S 16
R 4 W
1963

from which the remains of an original bearing tree

A root hole, bears S. 10° E., 141 lks. dist., with
a down oak alongside, 10 ins. diam., with axe
marks visible on open blaze.

and bearing trees mkd. by Godfrey

A grand fir, 16 ins. diam., bears N. 44 1/2° E., 37 lks.
dist., with healed blaze.

A fir, 17 ins. diam., bears S. 9 3/4° E., 26 lks., dist.,
with healed blaze.

A fir, 15 ins. diam., bears S 50 1/2° W., 31 lks. dist.,
with healed blaze.

A cedar, 38 ins. diam., bears N. 31° W., 21 lks. dist.,
with healed blaze.

Land, mountainous
Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder, chinqu-
apin, and ash; undergrowth, salal, vine maple, poison oak,
rhododendron, Oregon grape, and fern.

N. 0° 05' E., bet. secs. 8 and 9.

Ascend 135 ft. over SE slope, through scattering timber and
moderate undergrowth.

8.10 Spur, slopes E.; asc. 85 ft. over SE slope.

19.92 Point for the S 1/16 sec. cor. of secs. 8 and 9.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the
ground, in a mound of stone, 3 ft. base, to top, with brass cap
mkd.

S 1/16
S 8 | S 9
1979

from which

A fir, 9 ins. diam., bears S. 74° E., 44 1/2 lks. dist.,
mkd. S 1/16 S9 BT.

A grand fir, 13 ins. diam., bears S 45 1/2° W., 47 lks.
dist., mkd. S 1/16 S8 BT.

Ascend 335 ft. over SW slope.

26.00 Begin steep ascent through large boulders.

39.84 Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate
distance; there is no remaining evidence of the original corner.