

County Surveyor's Record, Douglas County, Oregon

1400

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 4 W
1/4
S 8 | S 9
1979

from which

A basalt boulder, 6 x 6 x 5 ft. above ground, bears N. 53 1/2° E., 33 1/2 lks. dist., mkd. X BO on W. face.

A fir, 6 ins. diam., bears S 1/2° W., 12 lks. dist., mkd. 1/4 S8 BT.

Ascend 160 ft. over SW slope.

51.50 Spur, slopes W.; desc. 200 ft. over NW slope.

68.70 Bottom of descent, slopes W.; asc. 55 ft. over SW slope.

79.68 The cor. of secs. 4, 5, 8, and 9, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S
S 5 | S 4
S 8 | S 9
R 4 W
1963

from which the remaining original bearing trees

A fir, 60 ins. diam., bears N. 40° E., 49 lks. dist., with healed blaze, remarked by Godfrey with fragmentary scribe marks visible on bark blaze. (Record, 52 lks.)

A madrone, 16 ins. diam., bears S. 18° W., 86 lks. dist., with axe marks visible on decayed blaze. (Record, 90 lks.)

and bearing trees mkd. by Godfrey

A fir, 10 ins. diam., bears S. 14° E., 54 1/2 lks. dist., with healed blaze.

A fir, 9 ins. diam., bears S. 61° W., 39 lks. dist., with healed blaze.

A fir, 30 ins. diam., bears N. 78° W., 38 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder, chinquapin, and ash; undergrowth, salal, vine maple, poison oak, rhododendron, Oregon grape, and fern.

From the cor. of secs. 3, 4, 9, and 10,