

County Surveyor's Record, Douglas County, Oregon

16401

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

S. 89° 49' W., bet. secs. 4 and 9.

Ascend 160 ft. over SE slope, through heavy timber and dense undergrowth.

6.70 Spur, slopes N. 70° E.; desc. 20 ft. over NW slope.

19.50 Creek, 2 lks. wide, course N. 25° E.; asc. 500 ft. over NE slope.

39.90 The 1/4 sec. cor. of secs. 4 and 9, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S

1/4 $\frac{S\ 4}{S\ 9}$

R 4 W

1963

from which the remains of the original bearing tree

A root hole, bears N. 6° W., 5 lks. dist., with a down fir alongside, 15 ins. diam., with healed blaze.

A root hole, bears S. 25° E., 39 lks. dist., with a down fir, alongside, 33 ins. diam., with fragmentary scribe marks visible on open blaze.

and the remains of a bearing tree mkd. by Godfrey

A root hole, bears S. 37° E., 59 lks. dist., with a down fir alongside, 25 ins. diam., with healed blaze.

and new bearing trees

A chinquapin, 6 ins. diam., bears N. 4 1/2° E., 22 1/2 lks. dist., mkd. 1/4 S4 BT on bark blaze.

A chinquapin, 9 ins. diam., bears S. 42 1/2° E., 15 1/2 lks. dist., mkd. 1/4 S9 BT on bark blaze.

S. 89° 53' W., beginning new measurement.

Ascend 770 ft. over NE slope.

37.10 Rocky ridge, bears N. 15° W. and S. 15° E.; desc. 140 ft. over SW slope.

39.62 The cor. of secs. 4, 5, 8, and 9.

Land mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder, chinquapin, and ash; undergrowth, salal, vine maple, rhododendron, Oregon grape, and fern.

From the 1/4 sec. cor. of secs. 4 and 5, perpetuated and recorded by Milo E. Godfrey, Douglas County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.