

# County Surveyor's Record, Douglas County, Oregon

16402

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

T 24 S  
1/4  
S 5 | S 4  
R 4 W  
1963

from which the remains of the original bearing trees

A sawed fir stump, 25 ins. diam., bears N. 62° E., 14 lks. dist., with healed blaze.

A sawed fir stump, 13 ins. diam., bears S. 86° W., 6 lks. dist., with fragmentary scribe marks visible on open blaze. (Record, 4 lks.)

and the remains of a bearing trees mkd. by Godfrey

A root hole, bears S. 31° W., 28 lks. dist., with a down fir alongside, 22 ins. diam., no marks visible.

and a new bearing tree

A sawed fir stump, 15 ins. diam., bears S. 64 1/2° W., 9 1/2 lks. dist., mkd. 1/4 S5 BT.

No other suitable accessories available within limits.

N. 0° 44' W., bet. secs. 4 and 5.

Ascend 85 ft. over SE slope, through open logged area.

20.045 Point for the N 1/16 sec. cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16  
S 5 | S 4  
1979

from which

A fir, 16 ins. diam., bears S. 53 1/4° E., 232 lks. dist., mkd. N 1/16 S4 BT.

A fir, 13 ins. diam., bears N. 63° W., 95 lks. dist., mkd. N 1/16 S5 BT.

Ascend 5 ft. over SE slope.

21.00 Spur, slopes N. 45° E.; desc. 710 ft. over precipitous N. slope.

39.43 The original closing cor. of secs. 4 and 5, perpetuated and recorded by Mile E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 24 S  
R 4 W  
S 5 | S 4  
C C  
1963