

# County Surveyor's Record, Douglas County, Oregon

16403

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 24 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

from which an original bearing tree

A maple, 34 ins. diam., bears S. 40° E., 38 lks.  
dist., with healed blaze. (Record, 36 lks.)

and bearing trees mkd. by Godfrey

A grand fir, 22 ins. diam., bears S. 1° E., 86 lks.  
dist., with healed blaze.

A cedar, 15 ins. diam., bears S. 76° W., 131 lks.  
dist., with healed blaze.

39.50 Intersect the S. bdy. of sec. 32, T. 23 S., R. 4 W.

True point for the closing cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 23 S R 4 W  
S 32  
S 5 | S 4  
C C  
T 24 S R 4 W  
1979

from which

A basalt boulder, 2 1/2 x 2 1/2 x 2 ft. above ground,  
bears S. 56 1/2° E., 9 lks. dist., mkd. X BO on top.

A basalt boulder, 2 1/2 x 1 x 1 ft. above ground, bears  
S. 19° W., 9 lks. dist., mkd. X BO on top.

From this point, the cor. of secs. 32 and 33 only, T 23 S. R. 4 W.,  
bears S. 89° 44' E., 2.74 chs. dist., hereinbefore described.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone, ash, chinqu-  
apin, and alder; undergrowth, salal, poison oak, Oregon grape,  
vine maple, rhododendron, and fern.

From the cor. of secs. 28, 29, 32, and 33.

S. 89° 07' W., bet. secs. 29 and 32.

Ascend 5 ft. over SE slope, through scattering timber and light  
undergrowth.

1.30 Ridge, bears N. 30° E. and S. 30° W., desc. 160 ft. over SW slope.

13.15 Ravine, drains S. 20° E., asc. 35 ft. over SE slope.

20.065 Point for the E 1/16 sec. cor. of secs. 29 and 32.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

E 1/16 S 29  
S 32  
1979