

# County Surveyor's Record, Douglas County, Oregon

16108

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 24 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

From the cor. of secs. 4, 5, 8, and 9.

S. 89° 37' W., bet, secs, 5 and 8.

Descend 470 ft. over broken SW slope, through heavy timber and dense undergrowth.

16.55 Ravine, drains N. 35° W.; asc. 15 ft. over SE slope.

19.61 Point for the E 1/16 sec. cor. of sec. 5 only.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 S 5  
1979

from which

A fir, 11 ins, diam., bears N. 71° E., 23 lks. dist.,  
mkd. E. 1/16 S5 BT.

A fir, 10 ins. diam., bears N. 83° W., 118 lks. dist.,  
mkd. X BT.

and a bearing tree of which I have no record

A fir, 9 ins. diam., bears S., 32° W., 83 1/2 lks.  
dist., with scribe marks E 1/16 S8 BT visible  
on open blaze.

Set a 5 ft. steel fence post alongside iron post.

Ascend 1 ft. over NE slope.

19.70 Top of ascent, slopes N.; desc. 205 ft. over SW slope.

39.45 The 1/4 sec. cor. of secs. 5 and 8, perpetuated and recorded by Milo E. Godfrey, Depty County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S  
1/4  $\frac{S 5}{S 8}$   
R 4 W  
1963

from which the remains of an original bearing tree

A root hole, bears N. 20° E., 112 lks. dist., with  
a down fir alongside, 30 ins. diam., with axe  
marks visible on decayed blaze.

and bearing trees mkd. by Godfrey

A cedar, 22 ins. diam., bears N. 44° E., 104 lks.  
dist., with healed blaze.

A fir, 21 ins. diam., bears S. 31° W., 181 lks.  
dist., with healed blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder,  
chinquapin, and ash; undergrowth, salal, rhododendron, vine maple,  
poison oak, Oregon grape, and fern.