

# County Surveyor's Record, Douglas County, Oregon

16410

Dependent Resurvey of a Portion of Boundaries of  
Donation Land Claim No. 46,  
T. 24 S., R. 4 W., Willamette Meridian, Oregon

## CHAINS

and a new bearing tree

A fir, 8 ins. diam., bears S. 53° W., 36 lks.  
dist., mkd. C 46 BT.

S. 89° 43' W., on the N. bdy of Claim No. 46.

Ascend 20 ft. over NE slope.

1.20 Ridge, bears N. 40° W. and S. 40° E.; desc. 180 ft. over broken  
SW slope.

15.72 Intersect the N. and S. center line of the SE 1/4 of sec. 15.

The crossing closing cor. of the N. and S. center line of  
the SE 1/4 of sec. 15, with the N. bdy. of Claim No. 46,  
established and recorded by Donald A. Bentz, Registered  
Land Surveyor No. 839, in 1979, and is accepted as the  
corner, monumented with an iron rod, 5/8 in. diam., firmly  
set, projecting 4 ins. above ground, from which a bearing  
tree mkd. by Bentz:

A fir, 23 ins. diam., bears N. 59 3/4° E., 6 1/2 lks.  
dist., with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

E  
CCC | S 15  
E  
DLC 46  
1979

from which a new bearing tree

A fir, 15 ins. diam., bears N. 10 1/2° W., 135 lks.  
dist., mkd. T24S R4W S15 CCC BT.

Reset iron rod alongside iron post.

From this point, the SE 1/16 sec. cor. of sec. 15, bears  
S. 0° 09' E., 7.58 chs. dist., hereinafter described.

S. 89° 43' W., beginning new measurement.

Descend 160 ft. over SW slope.

7.60 Bottom of descent, slopes S.; asc. 40 ft. over SE slope.

15.50 Spur, slopes S.; desc. 160 ft. over SW slope.

19.89 Intersect the N. and S. center line of sec. 15.

25.30 Creek, 1 lk wide, course S. 40° W.; desc. 35 ft. over broken  
SW slope.

27.55 Creek, 1 lk. wide, course S.; asc. 130 ft. over SE slope.

35.50 Spur, slopes S.; desc. 20 ft. over SW slope.