

# County Surveyor's Record, Douglas County, Oregon

16411

Dependent Resurvey of a Portion of Boundaries of  
Donation Land Claim No. 46,  
T. 24 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

36.70 Creek, 1 lk. wide, course S. 15° E.; asc. 50 ft. over SE. slope.

48.20 Spur, slopes S.; desc. 45 ft. over SW. slope.

52.00 Creek, 1 lk. wide, course S. 10° E.; asc. 40 ft. over SE slope.

54.96 The NW. cor. of Donation Land Claim No. 46, identical with the NE. cor. of Donation Land Claim No. 38, monumented with an iron rod, of which I have no record, 2 ins. diam., firmly set, projecting 2 ins. above ground. This position is harmoniously related to existing original corners, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 4 W  
S 15  
DLC 38 | DLC 46  
1979

from which

An oak, 10 ins. diam., bears S. 82 1/4° E., 61 lks. dist., mkd. C 46 BT.

A fir, 5 ins. diam., bears S. 45 3/4° W., 91 lks. dist., mkd. C 38 BT.

Reset iron rod alongside iron post.

From this point, the NW. cor. of Donation Land Claim No. 38, bears S. 89° 43' W., 40.19 chs. dist., perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1963, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 24 S R 4 W

NW | C 38  
DLC |  
1963

from which the remains of the original bearing trees

An oak stump, 15 ins. diam., bears S. 2 1/4° E., 1050 lks. dist., no marks visible.

An oak snag, 38 ins. diam., bears West, 142 lks. dist. with scribe marks BT visible on open blaze.

and bearing trees mkd. by Godfrey

An oak, 8 ins. diam., bears N. 37° E., 12 1/2 lks. dist., with healed blaze.

An oak, 14 ins. diam., bears S. 5° W., 29 lks. dist. with healed blaze.