

County Surveyor's Record, Douglas County, Oregon

16413

Subdivision of Section 15, T. 24 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 24 S R 4 W C 1/4 S 15 1979</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 27 3/4° W., 18 1/2 lks. dist., mkd. C 1/4 S 15 BT.</p> <p style="padding-left: 40px;">Reset iron rod alongside iron post.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>N 0° 12' W., beginning new measurement.</p> <p>Ascend 85 ft. over SW. slope.</p>
6.85	<p>Ridge, bears N. 30° W. and S. 30° E.; asc. 310 ft. over broken S. slope.</p>
20.025	<p>Point for the center N 1/16 sec. cor. of sec. 15.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} C \\ N \ 1/16 \ S \ 15 \\ C \\ 1979 \end{array}$ </p> <p>from which</p> <p style="padding-left: 40px;">A fir, 50 ins. diam., bears N. 52° E., 10 lks. dist., mkd. CN 1/16 S15 BT.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 82 1/2° W., 79 lks. dist., mkd. CN 1/16 S15 BT.</p> <p>Ascend 2 ft. over S. slope.</p>
21.15	<p>Ridge, bears E. and W.; desc. 85 ft. over NE. slope.</p>
23.00	<p>Gravelled road, 30 lks. wide, bears N. 65° W. and S 65° E.</p>
25.05	<p>Ravine, drains N. 80° E.; asc. 85 ft. over SE. slope.</p>
30.65	<p>Spur, slopes N. 80° E.; desc. 95 ft. over NE. slope.</p>
37.05	<p>Ravine, drains N. 80° E.; asc. 30 ft. over SE. slope.</p>
38.65	<p>Spur, slopes N. 40° E.; desc. 30 ft. over N. slope.</p>
40.05	<p>The 1/4 sec. cor. of secs. 10 and 15.</p>
1.30	<p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>S 89° 26' W., on the E. and W. center line of sec. 15.</p> <p>Ascend 15 ft. over NE. slope, through scattering timber and dense undergrowth.</p> <p>Spur, slopes N.; desc. 15 ft. over NW. slope.</p>