

County Surveyor's Record, Douglas County, Oregon

16415

Subdivision of Section 15, T. 24 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS

A fir, 8 ins. diam., bears S. $31\frac{1}{2}^{\circ}$ W., 28 $\frac{1}{2}$ lks.
dist. with scribe marks CW 1/16 S15 BT visible
on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

W 1/16
C ————— C
S 15
1979

Reset iron rod alongside iron post.

S. $89^{\circ} 26'$ W., beginning new measurement.

Descend 100 ft. over SW. slope.

5.80 Bottom of descent, slopes S.; asc. 65 ft. over SE. slope.

19.71 The $\frac{1}{4}$ sec. cor. of secs. 15 and 16.

From the E $\frac{1}{16}$ sec. cor. of secs. 15 and 22.

N. $0^{\circ} 09'$ W., on the N. and S. center line of the SE $\frac{1}{4}$
of sec. 15.

Ascend 30 ft. over SW. slope, through scattering timber
and dense undergrowth.

2.20 Ridge, bears N. 75° W. and S. 75° E.; desc. 40 ft. over
NE. slope.

5.65 Ravine, drains W.; asc. 20 ft. over SW. slope.

11.15 Ridge, bears N. 70° E. and S. 70° W.; desc. 5 ft. over
NW. slope.

13.90 Creek, 2 lks. wide, course W.; asc. 30 ft. over SW.
slope.

17.30 Head of ravine, drains W.; asc. 45 ft. over SW. slope.

19.95 Point for the SE $\frac{1}{16}$ sec. cor. of sec. 15, at inter-
section with the E. and W. center line of the SE $\frac{1}{4}$ of
sec. 15.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

SE $\frac{1}{16}$ S 15
1979

from which

An oak, 8 ins. diam., bears S. $28\frac{3}{4}^{\circ}$ E., 54 $\frac{1}{2}$ lks.
dist., mkd. SE $\frac{1}{6}$ S15 BT.

An oak, 12 ins. diam. bears N. 23° W., 64 $\frac{1}{2}$ lks.
dist., mkd. SE $\frac{1}{16}$ S15 BT.

Ascend 165 ft. over SW. slope.

27.53 Intersect the N. bdy. of Donation Land Claim No. 46.