

# County Surveyor's Record, Douglas County, Oregon

18420

T. 29 S., R. 9 W., Willamette Meridian, Oregon

## CHAINS

The following field notes describe the remonumentation of certain original corner points, township 29 south, range 9 west, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories, when Needed".

The remonumentation of original corner points was made at the request of the Coos Bay District Manager for administrative purposes of the Bureau of Land Management.

The mean magnetic declination is 20° 30' E.

Subdivisions, T. 29 S., R. 9 W.  
Willamette Meridian, Oregon  
Remonumentations of Certain Original Corner Points.

(Remonumenting corners established by William M. Porter,  
S. S. Deputy Surveyor, in 1907-09)

The 1/4 sec. cor. of Secs. 21 and 22, monumented with the original basalt stone, 11 x 11 x 8 ins., firmly set 11 ins. in the ground, mkd. 1/4 on W. face, from which the remains of an original bearing tree:

A hemlock stump, 20 ins. diam., bears N. 87° W.,  
16 lks. dist., no marks visible. (Record, 40 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

*FDOK  
S. Minor  
9/96 M125-76*

T 29 S R 9 W  
1/4  
S 21 S 22  
1978

from which new bearing trees

A fir, 5 ins. diam., bears N. 65° E., 26 lks.  
dist., mkd. 1/4 S22 BT.

A fir, 4 ins. diam., bears N. 38° W., 16 1/2 lks.  
dist., mkd. X BT.

Deposit corner stone alongside iron post.

The 1/4 sec. cor. of secs. 21 and 28, perpetuated and recorded by Ronald E. Stuntzner, Professional Engineer No. 6245, in 1972, monumented with a fir post, 6 ins. diam., firmly set, projecting 5 ft. above ground, from which the remains of the original bearing trees:

A sawed fir stump, 34 ins. diam., bears N. 30° E.,  
5 lks. dist., with scribe marks 1/4 S21 BT visible  
on opened blaze. (Record, N. 20° E.)

A sawed fir stump, 46 ins. diam., bears S. 11° E.,  
47 lks. dist., with scribe marks 1/4 S28 BT visible  
on opened blaze. (Record, S. 20° E.)

At the corner point