

# County Surveyor's Record, Douglas County, Oregon

16421

Remonumentation of Certain Original Corner Points,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon

**CHAINS**

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 9 W  
1/4  $\frac{S\ 21}{S\ 28}$   
1977

from which new bearing trees

A fir, 10 ins. diam., bears N. 40° W., 35 lks. dist., mkd. 1/4 S21 BT.

A fir, 10 ins. diam., bears S. 0 1/2° E., 80 lks. dist., mkd. 1/4 S28 BT.

Reset fir post alongside iron post.

(Remonumenting a corner established by W. S. Chapman, U. S. Deputy Surveyor, in 1875)

The 1/4 sec. cor. of secs. 4 and 9, determined at record bearing and distance from the remains of the original bearing trees:

A sawed fir stump, 20 ins. diam., bears N. 51° W., 26 lks. dist., with scribe marks BT visible on bark.

A fir, 35 ins. diam., bears S. 63° W., 16 lks. dist., with scribe marks 1/4 S9 T visible on bark.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 9 W  
1/4  $\frac{S\ 4}{S\ 9}$   
1977

from which new bearing trees

A fir, 8 ins. diam., bears N. 59° W., 156 lks. dist., mkd. 1/4 S4 BT.

A yew, 10 ins. diam., bears S. 2° E., 53 lks. dist., mkd. 1/4 S9 BT.

**PLEASE NOTE:**

*Certain corners in this set of field notes were not typed in the Douglas County records. These corners were in Coos County.*

*Corners in Douglas County and/or within a one-half mile range of the County line in Coos County were typed in the records of Douglas County.*

V. Laugen