

# County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey of a Portion  
of the South Boundary  
T. 29 S., R. 7 W., Willamette Meridian, Oregon

16124

CHAINS

(Restoring the survey by Nathaniel Ford,  
U. S. Deputy Surveyor, in 1854  
the resurvey by Fred Mensch,  
Cadastral Engineer, in 1924, and  
correcting the resurvey by Harvey E. Wofford,  
G. Steven Popken, and James J. Carlson,  
Cadastral Surveyors, in 1974-76)

Beginning at the cor. of secs. 34 and 34 1/2 only, on the S.  
bdy. of the Tp., monumented with an iron post, 3 ins. diam.,  
firmly set, projecting 9 ins. above ground, with brass cap  
mkd.

T 29 S R 7 W  
S 34 | S 34 1/2  
1924

from which the remains of the original bearing trees

A black oak, 28 ins. diam., bears N. 59° E., 53  
lks. dist., no marks visible.

A decayed black oak stump, 40 ins. diam., bears  
S. 2° E., 157 lks, dist., no marks visible.

and bearing trees mkd. by Mensch

A fir, 11 ins. diam., bears N. 51° E., 23 lks.  
dist., with healed blaze.

A fir, 28 ins. diam., bears N. 62° W., 42 lks.  
dist., with healed blaze.

N. 88° 02' W., along the S. bdy. of sec. 34, marking  
and blazing the true line.

Ascend 40 ft. over SE slope, through light timber and under-  
growth.

2.85 Spur, slopes S. 10° W.; desc. 40 ft. over SW slope.

6.60 Ravine, drains S.; asc. 65 ft. over SE. slope.

11.75 Spur, slopes S. 10° W.; desc. 190 ft. over SW. slope .

19.52 A corner established and recorded by Howard W. Johnstone,  
Registered Land Surveyor No. 498, in 1980, monumented with  
an iron rod, 5/8 in. diam., firmly set, projecting 6 ins.  
above ground, with an aluminum cap, 2 ins. diam., mkd. T29S  
R7W S34 ONLY E 1/16 LS 498, from which bearing trees mkd.  
by Johnstone:

A fir, 28 ins. diam., bears N. 76° E., 28 lks. dist.,  
with scribe marks 1/16 S34 BT visible on open blaze.

A madrone, 24 ins. diam., bears N. 15° W., 10 lks.  
dist., with scribe marks 1/16 S34 BT visible on  
open blaze.

Descend 40 ft. over SW. slope.

21.60 Ravine, drains S. 40° W.; asc. 25 ft. over SE. slope.

25.00 Spur, slopes S. 15° W.; desc. 45 ft. over SW. slope.