

County Surveyor's Record, Douglas County, Oregon

16429

T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, the Special Instructions, dated February 10, 1977, under Group Number 926, and the Special Instructions, dated May 12, 1978, and Supplemental Special Instructions, dated October 12, 1978, under Group Number 958, Oregon.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming a closure were measured twice to preclude error. Only those lines bounding or crossing public lands were blazed.

The geographic position of the corner of sections 10, 11, 14, and 15, as scaled from the Tye, Oregon quadrangle map, published by the United States Geological Survey, in 1955, is as follows:

Latitude 43° 24.2' N. Longitude 123° 37.4' W.

The mean magnetic declination is 20° 00' E.

Dependent Resurvey of a portion of the South Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the survey by Dennis Hathorn, U. S. Deputy Surveyor, in 1857, the retracement and survey by William H. Byars, U. S. Deputy Surveyor, in 1878, the retracement by Samuel C. Flint, U. S. Deputy Surveyor, in 1881, the resurvey by Henry L. Chandler, U. S. Deputy Surveyor, in 1893, the retracement by Morris Wygant, Compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, in 1911, the resurvey and remonumentation by Harold D. Corbin, Cadastral Surveyor, in 1959, and the resurvey by C. Albert White and Donald R. Beck, Cadastral Surveyor, in 1962.)

Beginning ^{at} the cor. of Tps. 24 and 25 S., Rs., 7 and 8 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

T 24 S
R 8 W R 7 W
S 36 | S 31
S 1 | S 6
T 25 S
1959

from which the remains of an original bearing tree