

County Surveyor's Record, Douglas County, Oregon

16430

Dependent Resurvey of a Portion of the South Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A sawed fir stump, 36 ins. diam., bears S. 40° E., 88 lks, dist., with axe marks visible on opened blaze.

and bearing trees mkd. by Corbin

A grand fir, 14 ins. diam.; bears N. 47° E., 31 lks. dist., with healed blaze. (Record, hemlock, 36 lks.)

A grand fir, 21 ins. diam., bears S. 74° E., 20 1/2 lks. dist., with healed blaze. (Record, hemlock, 22 lks.)

A fir, 14 ins. diam., bears S. 40 1/2° W., 58.1lks dist., with healed blaze. (Record, 60 lks.)

An alder, 14 ins. diam., bears N. 71° W., 41 lks. dist., with healed blaze. (Record, 44 lks.)

S. 89° 22' W., bet. secs. 1 and 36, marking and blazing the true line.

Descend 130 ft. over NW. slope, through heavy timber and dense undergrowth.

5.40 Little Wolf Creek, 40 lks, wide, course N. 40° E.; asc. 425 ft. over NE. slope.

6.65 Gravelled road, 30 lks. wide, bears N. 10° W. and S. 10° E.

27.35 Spur, slopes N. 30° E.; desc. 25 ft. over NW. slope.

33.50 Ravine, drains N.; asc. 15 ft. over NE. slope.

38.30 Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 8 W

1/4 $\frac{S\ 36}{S\ 1}$

T 25 S

1979

from which

A fir, 6 ins. diam., bears N. 74 1/4° W., 35 lks. dist., mkd. 1/4 S36 BT.

A fir, 4 ins. diam., bears S. 2° W., 17 1/2 lks. dist., mkd. 1/4 S1 BT.

Ascend 10 ft. over NE. slope.

44.00 Spur, slopes N. 70° W.; desc. 115 ft. over SW. slope

56.30 Head of ravine, drains S. 30° E.; asc. 170 ft. over E. slope.

63.75 Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.

75.00 Dirt road, 15 lks. wide, bears N. 15° W. and S. 15° E.