

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon

16431

CHAINS

76.30 Spur, slopes N. 20° W.; desc. 5 ft. over SW slope.

76.60 The cor. of secs. 1, 2, 35, and 36, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, and further perpetuated by Bruce R. Rogers, Deputy County Surveyor, in 1965, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.,

COUNTY SURVEYORS OFFICE

T	24	S	R
S	35	S	36
S	2	S	1
T	25	S	W
1958			

from which the remains of the original bearing trees

A root hole, bears N. 40° E., 15 lks. dist., with a down fir alongside, 40 ins. diam., with decayed blaze, no marks visible.

A fir snag, 40 ins. diam., bears S. 5° W., 20 lks. dist., with fragmentary scribe marks visible on bark.

and the remains of bearing trees mkd. by Byron

A fir, 14 ins. diam., bears N. 65 1/2° E., 81 lks. dist., with healed blaze.

A fir, 28 ins. diam., bears S. 58 1/2° E., 95 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears S. 67° W., 19 1/2 lks. dist., with healed blaze.

A cedar snag, 32 ins. diam., bears N. 38° W., 38 lks. dist., with scribe marks T24S R8W S35 CS BT visible on open blaze.

and bearing trees mkd. by Rogers

A fir, 14 ins. diam., bears S. 77° E., 16 lks. dist., with healed double blaze.

A grand fir, 14 ins. diam., bears S. 35° W., 31 lks. dist., with healed blaze.

A fir, 11 ins. diam., bears N. 63° W., 34 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, alder, maple, madrone, oak, and chinquapin; undergrowth, salal, fern, poison oak, hazel, Oregon grape, blackberry, arrowood, vine maple, and young timber.

From the cor. of secs. 32 and 33 only, determined at record bearing and distance from the remains of the original bearing trees:

A sawed fir stump, 60 ins. diam., bears S. 60° E., 31 lks. dist., no marks visible.