

County Surveyor's Record, Douglas County, Oregon

16432

Dependent Resurvey of a Portion of the South Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 52 ins. diam., bears N. 42° W., 91 lks. dist., with scribe marks T24S R8W S32 BT visible on bark.

and bearing trees mkd. by White and Beck

A hemlock, 26 ins. diam., bears N. 30° E., 149 lks. dist., with scribe marks T24S R8W S33 BT visible on open blaze.

A fir, 62 ins. diam., bears N. 16 1/2° W., 133 lks. dist., with scribe marks T24S R8W S32 BT visible on pitched over blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 8 W
S 32 | S 33
S 4
T 25 S R 8 W
1979

S. 89° 36' W., along the S. bdy. of sec. 32.

Descend 10 ft. over W. slope, through open logged area.

- .50 Junction of Case Knife Creek, 2 lks. wide, course N. 40° E., from S., and S. 40° W.; asc. 125 ft. over SE. slope, also enter timber, edge bears N. 40° E. and S. 40° W.
- 2.92 True point for the closing cor. of secs. 4 and 5, T. 25 S., R. 8 W., hereinafter described.

Ascend 95 ft. over SE. slope.
- 5.60 Spur. slopes N. 40° E.; desc. 130 ft. over NW. slope.
- 13.20 Creek, 2 lks. wide, course N. 60° E.; asc. 205 ft. over SE. slope.
- 21.45 Spur, slopes S.; desc. 20 ft. over SW. slope.
- 23.62 A corner established and recorded by Henry R. Reppeto, Registered Land Surveyor No. 618, in 1975, for Weyerhaeuser Co., monumented with a brass tablet, 2 ins. diam., set in a sandstone outcropping, 20 x 15 x 10 ft., above ground with top mkd.

$$\frac{E \ 1/16}{S \ 5}$$

from which bearing trees mkd. by Reppeto

A fir, 13 ins. diam., bears S. 25° E., 78 lks. dist., with scribe marks E. 1/16 S5 BT visible on open blaze.

A fir, 57 ins. diam., bears S. 21° W., 43 1/2 lks. dist., with illegible scribe marks visible on pitched over blaze.
- 23.30 Creek, 2 lks. wide, course S. 40° E.; asc. 20 ft. over NE. slope.