

County Surveyor's Record, Douglas County, Oregon

16433

Dependent Resurvey of a Portion of the South Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

- 24.30 Spur, slopes S. 80° E.; asc. 75 ft. along S. slope.
- 27.43 Point for the E 1/16 sec. cor. of sec. 5 only, T. 25 S., R. 8 W., hereinafter described.

Ascend 5 ft. along S. slope.
- 28.65 Ravine, drains S. 50° E.; asc. 305 ft. over SE. slope.
- 34.65 Head of ravine, drains S. 85° E.; asc. 230 ft. over E. slope.
- 39.95 Ridge, bears N. 20° E. and S. 20° W.; desc. 20 ft. over SW. slope.
- 40.55 Dirt road, 20 lks. wide, bears N. and S.
- 41.22 The 1/4 sec. cor. of sec. 32 only, reestablished by proportionate measurement and recorded by Henry R. Reppeto, Registered Land Surveyor No. 618, in 1975, for Weyerhaeuser Co., and is accepted as the best available evidence of the position of the original corner, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

S 1/4
S 32

from which the remains of bearing trees mkd. by Reppeto

A fir snag, 10 ins. diam., bears N. 50 1/2° E., 85 lks. dist., with scribe marks 1/4 S32 BT visible on open blaze.

A fir, 70 ins. diam., bears N. 30° W., 112 lks. dist., with scribe marks 1/4 S32 BT visible on bark.

and a new bearing tree

A fir, 20 ins. diam., bears N. 40° E., 112 lks. dist., mkd. 1/4 S32 BT.

S. 89° 38' W., beginning new measurement.

Descend 90 ft. over SW. slope.

- 3.14 A corner established and recorded by Henry R. Reppeto Registered Land Surveyor No. 618, in 1975, for Weyerhaeuser Co., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.

N 1/4
S 5

from which bearing trees mkd. by Reppeto

A fir, 58 ins. diam., bears S. 42° E., 44 lks. dist., with scribe marks 1/4 S5 BT on bark.

A fir, 30 ins. diam., bears S. 21° W., 64 lks. dist., with scribe marks 1/4 S5 BT on bark.

- 5.67 Point for the 1/4 sec. cor. of sec. 5 only, T. 25 S., R 8 W., hereinafter described.