

# County Surveyor's Record, Douglas County, Oregon

16434

Dependent Resurvey of a Portion of the South Boundary,  
T. 24 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Descend 375 ft. over SW. slope.

12.60 Leave timber, enter logged area, edge bears S. and W.

20.60 Ravine, drains N. 45° W.; asc. 70 ft. over SE. slope.

22.70 Spur. slopes S.; desc. 245 ft. over SW. slope.

41.11 The cor. of secs. 31 and 32 only, determined at record bearing and distance from the remains of an original bearing tree.

A decayed fir snag, 40 ins. diam., bears N. 25° E.,  
56 lks, dist., with scribe marks 8W BT visible  
on decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 8 W  
S 31 S 32  
T 25 S R 8 W  
S 5  
1979

from which new bearing trees

A hemlock, 8 ins. diam., bears N. 34° E., 82 lks.  
dist., mkd. T24S R8 W S32 BT.

A hemlock, 11 ins. diam., bears N. 2 1/2° W., 51 lks.  
dist., mkd. T24S R8W S31 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, maple, madrone, hemlock, chinquapin, and alder; undergrowth, rhododendron, Oregon grape, fern, blackberry, arrowwood, hazel, salal, salmonberry, and huckleberry.

S. 89° 52' W., along the S. bdy. of sec. 31.

Descend 85 ft. over NW. slope, through open logged area.

0.12 From this point, a corner established and recorded by Henry R. Reppeto, Registered Land Surveyor No. 618, in 1975, for Weyerhaeuser Co., bears North 0.06 chs. dist., monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

S W  
S 32

from which the remains of bearing tree mkd. by Reppeto

A cedar, 14 ins. diam., bears N. 72° E., 23 lks.  
dist., with scribe marks S32 BT visible on  
open blaze.

A sawed cedar stump, 10 ins. diam., bears  
N 51° W., 30 lks. dist., with scribe marks S31 BT  
visible on open blaze.

3.48 True point for the closing cor. of secs. 5 and 6,  
T. 25 S., R. 8 W., hereinafter described.