

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon

16435

CHAINS

- Descend 15 ft. over NW. slope.
- 3.50 Enter timber, edge bears S. and W.
- 4.30 Creek, 1 lk. wide, course N. 30° W.; desc. 5 ft. over NW. slope.
- 7.55 Spur, slopes N. 35° W.; desc. 140 ft. over NW. slope.
- 9.60 Creek, 2 lks. wide, course N. 35° W.; asc. 10 ft. over NE. slope.
- 10.20 Spur, slopes N. 20° W.; desc. 40 ft. over NW, slope.
- 12.35 Creek, 2 lks. wide, course N. 20° W.; asc. 35 ft. over NE. slope.
- 13.20 Spur, slopes N. 20° W.; desc. 190 ft. over NW. slope.
- 23.15 Creek, 2 lks. wide, course N. 30° W.; asc. 55 ft. over NE. slope.
- 24.50 Spur, slopes N.; desc. 115 ft. over NW. slope.
- 28.30 Head of ravine, drains N.; asc. 10 ft. over NE. slope.
- 30.20 Spur, slopes N. 20° W.; desc. 115 ft. over NW. slope.
- 33.55 Creek, 5 lks. wide, course S. 45° W.; asc. 30 ft. over SE slope.
- 38.60 Spur, slopes S.; desc. 5 ft. over SW. slope.
- 39.38 Point for the 1/4 sec. cor. of sec. 31 only, determined by the method of irregular boundaries; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 24 S R 8 W
1/4 S 31
 T 25 S R 8 W
 1979
- from which
- A hemlock, 18 ins. diam., bears N. 38 1/2° E., 75 lks. dist., mkd. 1/4 S31 BT.
- A hemlock, 7 ins. diam., bears N. 83 1/2° W.; 36 lks. dist., mkd. 1/4 S31 BT.
-
- N. 89° 48' W., beginning new measurement.
- Descend 60 ft. over SW. slope.
- 2.20 Creek, 15 lks. wide, course S. 10° W.; asc. 55 ft. over SE. slope.
- 3.92 From this point, a corner established and recorded by Donald L. Peel, Registered Land Surveyor No. 752, in 1967, for Weyerhaeuser Co., bears South, 0.17 chs. dist., monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 4 ins. above ground, from which bearing trees mkd. by Peel: