

# County Surveyor's Record, Douglas County, Oregon

16436

Dependent Resurvey of a Portion of the South Boundary,  
T. 24 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 18 ins. diam., bears S. 6° W., 23 lks. dist., with a nail with "W" embossed on head and brass disc, 2 1/2 ins. diam., mkd. LS 752.

A cedar, 48 ins. diam., bears N. 66° W., 22 lks. dist., with a nail with "W" embossed on head, at base.

3.96 Point for the 1/4 sec. cor. of sec. 6 only, T. 25 S., R. 8 W., hereinafter described.

Ascend 50 ft. over SE. slope.

6.75 Creek, 1 lk. wide, course S. 45° E.; asc. 60 ft. over SE. slope.

9.85 Spur, slopes S.; desc. 40 ft. over broken SW. slope.

15.70 Ravine, drains S.; asc. 25 ft. over SE. slope.

20.70 Spur, slopes S.; desc. 10 ft. over SW. slope

21.94 Point for the cor. of Tps. 24 S. Rs. 8 and 9 W., at proportionate distance in departure, and at record distance in latitude, from the 1/4 sec. cor. of secs. 31 and 36, Tps. 24 S., Rs. 8 and 9 W.; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long. 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S
R 9 W   R 8 W
S 36   S 31
T 25 S   R 8 W
S 6
1979

from which

A fir, 16 ins. diam., bears N. 39 1/2° E., 36 lks. dist., mkd. T24S R8W S31 BT.

A fir, 12 ins. diam., bears N. 17° W., 51 lks. dist., mkd. T24S R9W S36 BT.

From this point, the 1/4 sec. cor. of secs. 31 and 36, T. 24 S., Rs. 8 and 9W., bears N. 3° 57' W., 40.09 chs. dist., determined at record distance from the remains of the original bearing trees:

A root hole, bears N. 58° E., 32 lks. dist., with a down yew alongside, 8 ins. diam., with illegible scribe marks visible on decayed blaze.

A root hole, bears N. 25° W., 32 lks. dist., with a down yew alongside, 9 ins. diam., no marks visible. (Record, N. 35° W.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S
1/4
R 9 W   R 8 W
S 36   S 31
1979