

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary,
T. 24 S., R. 8 W., Willamette Meridian, Oregon

16437

CHAINS

from which new bearing trees

A sawed cedar stump, 40 ins. diam., bears S. 63° E.,
69 lks. dist., mkd. 1/4 S31 BT.

A sawed fir stump, 48 ins. diam., bears S. 33° W.,
73 lks. dist., mkd. 1/4 S36 BT.

Corner is located in open logged area.

Land, mountainous.

Soil rocky clay.

Timber, fir, alder, hemlock, yew, maple, dogwood, and
madrone; undergrowth, hazel blackberry, arrowwood, fern,
vine maple, Oregon grape, salal, salmonberry, huckleberry,
and rhododendron.

Dependent Resurvey of a Portion of the South Boundary,
T. 24 S., R. 9 W., Willamette Meridian, Oregon

(Restoring the survey by William H. Byars,
U. S. Deputy Surveyor, in 1878,
and the retracement by Morris Wygant, Compassman for
Zachariah M. Derrik, U. S. Deputy Surveyor, in 1911)

From the cor. of Tps. 24 S., Rs. 8 and 9 W.

S. 88° 24' W., on the S. bdy. of sec. 36.

Descend 230 ft. over SW. slope, through heavy timber and
dense undergrowth.

- 13.15 Lake Creek, 20 lks. wide, course N.; asc. 130 ft. over
NE. slope.
- 15.25 Gravelled road, 35 lks. wide, bears N. 10° W. and
S. 10° E.
- 22.53 True point for the closing cor. of T. 25 S., R. 8 W.,
hereinafter described.

Ascend 20 ft. over NE. slope.
- 24.15 Ravine, drains N. 40° E.; asc. 150 ft. over NE. slope.
- 27.50 Spur, slopes N. 45° E.; asc. 20 ft. along N. slope.
- 29.50 Ravine, drains N. 55° E.; asc. 295 ft. over NE. slope.
- 33.70 Dirt road, 15 lks. wide, bears N. 20° W. and S. 20° E.
- 35.25 Spur, slopes N.; desc. 195 ft. over NW. slope.
- 40.07 Point for the 1/4 sec. cor. of sec. 36 only, determined by
the method of irregular boundaries; there is no remaining
evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 24 S R 9 W
1/4 S 36
1979