

County Surveyor's Record, Douglas County, Oregon

16439

T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Dependent Resurvey of a Portion of the West Boundary,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the survey by Charles L. Campbell,
U. S. Deputy Surveyor, in 1902, and
the survey by Morris Wygant, Compassman for
Zachariah M. Derrick, U. S. Deputy Surveyor, in 1911)

From this corner established by Charles L. Campbell, in 1902, for the closing cor. of T. 25 S., Rs. 8 and 9 W., and changed to an angle point by Morris Wygant, in 1911, perpetuated and recorded by Donald L. Peel, Registered Land Surveyor No 752, in 1967, monumented with an iron pipe, 1/4 ins. diam., firmly set, projecting 6 ins. above ground, from which the original bearing trees:

A fir, 40 ins. diam., bears S. 61 3/4° E., 93 lks.
dist., with healed blaze. (Record, S. 30° E.)

A fir, 44 ins. diam., bears S. 30° W., 20 lks.
dist., with healed blaze, (Record, S. 61 3/4° W.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

A P
|
T 25 S
R 8 W
S 6
1978

from which a new bearing tree

A cedar, 11 ins. diam., bears N. 48° E., 74 lks.
dist., mkd. AP S6 BT.

N. 0° 12' E.; on the W. bdy. of sec. 6, marking and blazing the true line.

Ascend 20 ft. over SE. slope, through heavy timber and dense undergrowth.

- 2.20 Spur, slopes S. 75° E.; desc. 100 ft. over NE. slope.
- 4.30 Creek, 1 lk. wide, course N. 55° E.; asc. 65 ft. over SE. slope.
- 6.30 Spur, slopes E.; desc. 15 ft. over NE. slope.
- 7.30 Creek, 1 lk. wide, course S. 60° E.; asc. 150 ft. over SE. slope.
- 13.10 Spur, slopes E.; desc. 80 ft. over NE. slope.
- 15.45 Creek, 1 lk. wide, course E.; asc. 60 ft. over SE. slope.
- 18.65 Spur, slopes E.; desc. 5 ft. over NE. slope.
- 20.30 Spur, slopes N. 45° E.; desc. 315 ft. over NE. slope.
- 23.90 Top of rock bluff, 30 ft. high, edge bears E. and W.