

County Surveyor's Record, Douglas County, Oregon

16440

Dependent Resurvey of a Portion of the West Boundary,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

26.21

Intersect the S. bdy. of sec. 36, T. 24 S. R. 9 W.
True point for the closing cor. of T. 25 S., R. 8 W.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 9 W
S 36
T 25 S
R 8 W
S 6
C C
1979

from which

A hemlock, 36 ins. diam., bears S. 51 1/2° E., 99 lks. dist., mkd. T25 S R8 W S6 CC BT.

A cedar, 35 ins. diam., bears S. 73° E., 265 lks. dist., mkd. T25S R8W S6 CC BT.

From this point, the closing cor. of T. 25 S., Rs. 8 and 9 W., established by Morris Wygant, in 1911, bears N. 0° 12' E., 0.05 chs. dist., perpetuated and recorded by Vernon R. Tracy, County Surveyor, in 1970, determined at record bearing and distance from the remains of an original bearing tree:

A sawed cedar stump, 16 ins. diam., bears S. 60° E., 78 lks. dist., with illegible scribe marks visible on opened blaze and remarked by Tracy T25S R8W S6 CC CS BT on open blaze.

and a bearing tree mkd. by Tracy

A hemlock, 18 ins. diam., bears S. 13° W., 40 lks. dist., with scribe marks CC CS BT visible on partially open blaze.

From this same point, the 1/4 sec. cor. of sec. 36 only, T. 24 S., R. 9 W., bears S. 88° 24' W., 17.54 chs. dist., hereinbefore described.

Land, mountainous.
Soil, rocky clay.
Timber, fir, hemlock, cedar, yew maple, madrone, and alder; undergrowth, vine maple, hazel, arrowwood, Oregon grape, salal, blackberry, young timber, and fern.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the survey by Samuel C. Flint,
U. S. Deputy Surveyor, in 1881,
the retracement and survey by Morris Wygant, Compassman
for Zachariah M. Derrik, U. S. Deputy Surveyor, in 1911,
and the resurvey and remonumentation by Donald R. Beck
and John M. Jelley, Cadastral Surveyors, in 1964-65)

From the cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.