

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

16441

CHAINS

T 25 S R 8 W
S 2 | S 1
S 11 | S 12
1964

from which the remaining original bearing trees

A fir, 60 ins. diam., bears S. 20° E., 85 lks. dist., with fragmentary scribe marks visible on bark blaze.

A fir, 45 ins. diam., bears S. 63° W., 85 lks. dist., with fragmentary scribe marks visible on bark blaze. (Record, S. 60° W.)

and bearing trees mkd. by Beck and Jelley

A fir, 25 ins. diam., bears N. 40 3/4° E., 63 lks. dist., with healed blaze. (Record, N. 42° E.)

A fir, 24 ins. diam., bears S. 71° E., 7 lks. dist., with healed blaze.

A fir, 12 ins. diam., bears S. 56 1/4 W., 44 lks. dist., with healed blaze. (Record, S. 57 1/2° W.)

A fir, 17 ins. diam., bears N. 61° W., 50 lks. dist., with healed blaze.

N. 1° 34' E., bet. secs. 1 and 2, marking and blazing the true line.

Descend 75 ft. over NE. slope, through heavy timber and dense undergrowth.

- 5.20 Little Wolf Creek, 30 lks. wide, course E.; asc. 280 ft. over SE. slope.
 - 6.65 Gravelled road, 30 lks., wide, bears E. and W.
 - 18.20 Spur, slopes E.; desc. 25 ft. over NE. slope.
 - 23.20 Ravine, drains S. 80° E.; asc. 35 ft. over SE. slope.
 - 24.95 Spur, slopes E.; desc. 10 ft. over NE. slope.
 - 29.05 Ravine, drains S. 45° E.; asc. 75 ft. over SW. slope.
 - 32.20 Dry creek bed, 4 lks. wide, course S. 40° E.; asc. 55 ft. over SW. slope.
 - 34.76 Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S R 8 W
1/4
S 2 | S 1
1978

from which

A fir, 9 ins. diam., bears S. 86 1/2° E., 25 lks. dist., mkd. 1/4 S1 BT.