

County Surveyor's Record, Douglas County, Oregon

16444

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T 25 S R 8 W
S 3 | S 2
S 10 | S 11
1978

from which a bearing tree mkd. by Tracy

A fir, 19 ins. diam., bears S. 27° E., 49 lks.
dist., with healed blaze.

and bearing trees mkd. by Langlitz

A fir, 14 ins. diam., bears S. 45° W., 75 lks.
dist., with healed blaze.

A fir, 15 ins. diam., bears N. 52° W., 111 lks.
dist., with healed blaze.

and a bearing tree

A fir, 10 ins. diam., bears N. 71° E., 121 lks.
dist., mkd. T25S R8W S2 BT.

Land, mountainous.

Soil, rocky clay.

Timber, yew, fir, hemlock, maple, alder, cedar, madrone,
chinquapin, and dogwood; undergrowth, manzanita, fern,
blackberry, vine maple, hazel, willow, Oregon grape,
salal, huckleberry, arrowwood, and wild rose.

From the cor. of secs. 1, 2, 11, and 12.

S. 80° 23' W., bet. secs. 2 and 11.

Descend 75 ft. over NW. slope, through heavy timber and
dense undergrowth.

4.60 Little Wolf Creek, 25 lks. wide, course N. 25° E.; asc.
365 Ft. over SE. slope.

12.90 Gravelled road, 25 lks. wide, bears N. 55° E. and
S. 55° W.

30.45 Spur, slopes S. 30° E.; asc. 125 ft. over SE. slope.

37.70 Spur, slopes S. 30° E.; desc. 5 ft. over SW. slope.

38.94 Point for the 1/4 sec. cor. of secs. 2 and 11, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 25 S R 8 W
1/4 S 2
S 11
1979

Fd. Ok by B. Shaner
12/7/2000
C.S. File 65/33-19

from which

A grand fir, 8 ins. diam., bears N. 45° E., 29
lks. dist., mkd. 1/4 S2 BT.

A fir, 8 ins. diam., bears S. 6 1/2° W., 21 lks.
dist., mkd. 1/4 S11 BT.