

County Surveyor's Record, Douglas County, Oregon

16446

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T 25 S R 8 W

1/4 $\frac{S\ 10}{S\ 15}$

1979

from which

A fir, 12 ins. diam., bears N. 59° W., 18 lks.
dist., mkd. 1/4 S10 BT.

A fir, 10 ins. diam., bears S. 19° W., 43 lks.
dist., mkd. 1/4 S15 BT.

S. 89° 50' W., beginning new measurement.

Descend 170 ft. over slope.

7.25 Creek, 3 lks. wide, course S. 10° W.; asc. 80 ft. over SE. slope.

8.80 Spur. slopes S. 5° W; desc. 20 ft. over SW. slope.

9.75 Ravine, drains S. 10° E.; asc. 65 ft. over SE. slope.

11.55 Spur, slopes S.; desc. 5 ft. over SW. slope.

19.59 The W 1/16 cor. of secs. 10 and 15, established by Roseburg Lumber Co., in 1963, and is accepted as the corner, monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

W 1/16 $\frac{S\ 10}{S\ 15}$

1979

from which

A fir, 8 ins. diam., bears N. 2° E., 35 lks.
dist., mkd. W 1/16 S10 BT.

A fir, 12 ins. diam., bears S. 17° W., 26 lks.
dist., mkd. W 1/16 S15 BT.

S. 89° 50' W., beginning new measurements.

Descend 50 ft. over SW. slope.

9.70 Creek, 21ks. wide, course S. 20° W.; asc. 25 ft. along S. slope.

18.45 Top of ascent, slopes S. 30° W.; desc. 15 ft. over NW. slope.

19.59 The cor. of secs. 9, 10, 15, and 16, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1960, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.