

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

16447

CHAINS

COUNTY SURVEYORS OFFICE

T 25 S R 8 W

S 9 | S 10

S 16 | S 15

1960

from which the remains of an original bearing tree

A sawed fir stump, 42 ins. diam., bears S. 45° W.,
53 lks. dist., with scribe marks T25S R8 W S16 BT
visible on opened blaze.

and the remains of bearing trees mkd. by Wygant

A sawed fir stump, 40 ins. diam., bears N. 12 1/2° E.;
83 lks. dist., with scribe marks W S10 B visible
on opened blaze.

A fir, 23 ins. diam., bears S. 20° E., 29 lks.
dist., with healed blaze. (Record, 32 lks.)

and bearing trees mkd. by Byron

A maple, 12 ins. diam., bears N. 70° E., 39 lks.
dist., with healed blaze.

A fir, 10 ins. diam., bears S. 25° W., 37 lks.
dist., with healed double blaze.

A hemlock, 15 ins. diam., bears N. 43° W., 107
lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, yew, fir, hemlock, alder, maple, cedar, madrone,
and dogwood; undergrowth, manzanita, ferns, blackberry,
vine maple, hazel, willow, Oregon grape, salal, huckle-
berry, rhododendron, arrowweed, and wild rose.

N. 0° 11' E., bet. secs. 9 and 10.

Descend 25 ft. over NW. slope, through heavy timber and
dense undergrowth.

2.05 Creek, 2 lks. wide, course S. 60° W.; asc. 415 ft. over
SE. slope.

20.18 Point for the S 1/6 sec. cor. of secs. 9 and 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

S 1/16

S 9 | S 10

1979

from which

A fir, 12 ins. diam., bears S. 79 1/2° E.; 20 lks.
dist., mkd. S 1/16 S10 BT.

A fir, 9 ins. diam., bears N. 34° W., 17 lks.
dist., mkd. S 1/16 S9 BT.

Ascend 210 ft. over SE. slope.