

County Surveyor's Record, Douglas County, Oregon

16448

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

- 27.10 Ridge, bears N. 65° E. and S. 65° W.; desc. 425 ft. over N. slope.
- 36.75 Creek, 3 lks. wide, course N. 45° E.; asc. 35 ft. over SE. slope.
- 39.00 Spur, slopes N. 60° E.; desc. 10 ft. over NE. slope.
- 40.36 The 1/4 sec. cor. of secs. 9 and 10, perpetuated and recorded by Vernon R. Tracy, County Surveyor, in 1967, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 25 S
1/4
S 9 | S 10
R 8 W
1967

from which the original bearing trees

A fir, 38 ins. diam., bears N. 45° E., 35 lks. dist., with opened blaze, no marks visible.

A fir, 44 ins. diam., bears N. 53° W., 37 lks. dist., with healed blaze.

and bearing trees mkd. by Tracy

A fir, 8 ins. diam., bears N. 68 3/4° E., 35 lks. dist., with healed double blaze.

A fir, 7 ins. diam., bears S. 10 1/2° W., 12 lks. dist., with healed double blaze.

N. 1° 10' E., beginning new measurement

Descend 285 ft. over NE. slope.

- 11.80 Creek, 2 lks. wide, course N. 45° W.; asc. 20 ft. over SW. slope.
- 12.15 Spur, slopes W.; desc. 65 ft. over NW. slope.
- 19.00 Creek, 2 lks. wide, course N. 45° W.; asc. 25 ft. over SW. slope.
- 19.84 Point for the N 1/16 sec. cor. of secs. 9 and 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
S 9 | S 10
1979

from which

A fir, 6 ins. diam., bears N. 43° E., 30 lks. dist., mkd. N 1/16 S10 BT.

A fir, 12 ins. diam., bears S. 70° W., 5 lks. dist., mkd. N 1/16 S9 BT.

Ascend 5 ft. over SW. slope.