

# County Surveyor's Record, Douglas County, Oregon

16450

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 25 S., R. 8 W., Willamette Meridian, Oregon

**CHAINS**

- 9.10 Gravelled road, 20 lks. wide, bears N. 75° E. and S. 75° W.
- 20.80 Spur, slopes S.; desc. 75 ft. over SW. slope.
- 24.50 Gravelled road, 20 lks, wide, bears N. 60° W. and S. 60° E.
- 30.60 Little Wolf Creek, 12 lks. wide, course S. 75° E.; asc. 215 ft. over NE. slope.
- 38.35 Spur, slopes N.; desc. 5 ft. over NW. slope.
- 39.86 The 1/4 sec. cor. of secs. 3 and 10, perpetuated and recorded by Vernon R. Tracy, County Surveyor, in 1967, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 25 S  
1/4  $\frac{S\ 3}{S\ 10}$   
R 8 W  
1967

from which the remains of the original bearing trees

A fir stump, size indeterminate, bears N. 88° E., 156 lks. dist., no marks visible.

A root hole, bears S. 71° E., 7 lks. dist., with a down fir alongside, size indeterminate, no marks visible.

and the remains of bearing trees mkd. by Tracy

A fir snag, 8 ins. diam., bears N. 33° W., 10 lks. dist., with scribe marks 1/4 S3 CS BT visible. on open blaze.

A fir, 18 ins. diam., bears S. 27° E., 9 1/2 lks. dist., with healed blaze.

and a new bearing tree

A fir, 6 ins. diam., bears N. 48 1/2° W.; 23 lks. dist., mks. 1/4 S3 BT.

S. 89° 23' W., beginning new measurement.

Descend 165 ft. over NW. slope.

- 19.25 The W 1/16 sec. cor. of secs. 3 and 10, established by person(s) unknown, and is accepted as the corner, monumented with an iron pipe, 1 in. diam., firmly set, projecting 2 ins. above ground, from which bearing trees of which I have no record:

A fir, 21 ins. diam., bears N. 85° E., 6 lks. dist., with healed blaze.

An alder, 11 ins. diam., bears S. 20° W., 19 lks, dist., with open blaze, no mark visible.

At the corner point