

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

16451

CHAINS

Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins in the ground, directly over iron pipe, with brass cap mkd.

W 1/16 $\frac{S\ 3}{S\ 10}$
1979

from which new bearing trees

A fir, 34 ins. diam., bears N. 50° E., 40 lks. dist., mkd. W 1/16 S3 BT.

A fir, 18 ins. diam., bears S. 4 1/2° E., 50 lks. dist., mkd. W 1/16 S 10 BT.

S. 89° 23' W., beginning new measurement.

Descend 50 ft. over NW. slope.

4.70 Little Wolf Creek, 15 lks. wide, course N. 70° E.; asc. 215 ft. over SE. slope.

11.05 Gravelled road, 20 lks. wide, bears N. 60° E. and S. 60° W.

19.25 The cor. of secs. 3, 4, 9, and 10.

Land, mountainous.

Soil, rocky clay.

Timber, fir, madrone, cedar, maple, alder, hemlock, dogwood, chinquapin, and myrtle; undergrowth, manzanita, fern, blackberry, vine maple, hazel, willow, Oregon grape, salal, huckleberry, arrowwood, rhododendron, and wild rose.

From the cor. of secs. 8 and 17 only, perpetuated and recorded by Vernon R. Tracy, County Surveyor, in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap, mkd.

COUNTY SURVEYORS OFFICE

T 25 S
 S 8
S 17
R 8 W
1968

from which the remains of the original bearing trees

A root hole, bears S. 39 1/2° W., 46 lks. dist., with a down fir alongside, 40 ins. diam., no marks visible.

A fir, 48 ins. diam., bears N. 51° W., 58 lks. dist., with scribe marks S8 R8W visible in reverse and relief on overgrowth.

and bearing trees mkd. by Tracy

A hemlock, 15 ins. diam., bears S. 46 1/2° W., 32 lks. dist., with illegible scibe marks visible on partially healed blaze.

A hemlock, 12 ins. diam., bears N. 69 1/2° W., 25 lks. dist., with scribe marks T25S R8W S8 BT visible on open blaze.