

County Surveyor's Record, Douglas County, Oregon

16452

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

N. 0° 47' W., bet. secs. 8 and 16.

Ascend 15 ft. over S. slope, through heavy timber and dense undergrowth.

1.40 Ridge, bears N. 60° W. and S. 60° E.; desc. 65 ft. over NE. slope.

3.02 The cor. of secs. 9 and 16 only, perpetuated and recorded by Vernon R. Tracy, County Surveyor, in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 25 S
 | S 9
 | S 16
R 8 W
1968

from which the remains of the original bearing trees

A fir snag, 40 ins. diam., bears N. 21° E., 68 lks. dist., with scribe marks T25S R8 W S9 BT visible on opened blaze. (Record, 77 lks.)

A fir snag, 44 ins. diam., bears S. 89° E., 34 lks. dist., with scribe marks T25S R8W S16 BT visible on opened blaze.

and bearing trees mkd. by Tracy

A fir, 12 ins. diam., bears N. 57 1/2° E., 26 lks. dist., with healed blaze.

A cedar, 12 ins. diam., bears S. 69 1/2° E., 33 lks. dist., with scribe marks T25S R8W S16 BT visible on partially healed blaze.

North, bet. secs. 8 and 9, beginning new measurement.

Descend 285 ft. over NE. slope, through heavy timber and dense undergrowth.

5.90 Head of ravine, drains N. 30° W.; desc. 550 ft. over NW. slope.

22.75 Creek, 10 lks. wide, course N. 45° E.; asc. 395 ft. over SE. slope.

33.65 Spur, slopes E.; desc. 85 ft. over NE. slope.

35.90 Ravine, drains N. 80° E.; asc. 15 ft. over SE. slope.

36.34 The 1/4 sec. cor. of sec. 8 only, determined at record bearing and distance from the only remaining original bearing tree:

A fir, 63 ins. diam., bears S. 5° W., 21 lks. dist., with scribe mark 8 visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.