

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

16453

CHAINS

T 25 S R 8 W
1/4 |
S 8 |
1979

from which a new bearing tree

A fir, 6 ins. diam., bears N. 58° W., 11 lks.
dist., mkd. 1/4 S8 BT.

N. 0° 05' E., beginning new measurement.

Ascend 55 ft. over SE. slope.

2.77 The 1/4 sec. cor. of sec. 9 only, determined at record bearing and distance from the remains of an original bearing tree:

A root hole, bears N. 12° E.; 34 lks. dist., with
a down fir alongside, 62 ins. diam., with scribe
marks 1/4 S9 BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 25 S R 8 W
1/4 |
S 9 |
1979

from which new bearing trees

A fir, 9 ins. diam., bears N. 20 1/4° E., 8 1/2 lks.
dist., mkd. 1/4 S9 BT.

A fir, 5 ins. diam., bears S. 8° E., 36 lks.
dist., mkd. X BT.

N. 0° 05' E., beginning new measurement

Ascend 180 ft. over SE. slope.

3.70 Spur, slopes N. 65° E.; desc. 575 ft. over NW. slope.

15.35 Creek, 10 lks. wide, course N. 60° E.; asc. 35 ft. over SE. slope.

16.05 Spur, slopes S. 50° E.; desc. 20 ft. over NE. slope.

16.45 Creek, 2 lks. wide, course S. 50° E.; asc. 185 ft. over SE. slope.

20.45 Spur, slopes E.; desc. 5 ft. over NE. slope.

22.75 Ravine, drains S. 45° E.; asc. 240 ft. over SE. slope.

28.95 Spur, slopes E.; desc. 255 ft. over NE. slope.

35.55 Creek, 1 lk. wide, course E.; asc. 25 ft. over SE. slope.

36.54 The cor. of secs. 5 and 8 only, perpetuated and recorded by Vernon R. Tracy, County Surveyor, in 1967, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.