

County Surveyor's Record, Douglas County, Oregon

16455

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 56 ins. diam., bears N. 41° W., 104 lks. dist., with healed blaze.

N. 0° 54' W., bet. secs. 4 and 5, beginning new measurement.

Descend 10 ft. over NE. slope, through heavy timber and dense undergrowth.

- 1.40 Creek, 2 lks. wide, course E.; asc. 440 ft. over SE. slope.
- 10.30 Spur, slopes S. 65° E.; desc. 80 ft. over NE. slope.
- 14.60 Spur, slopes N. 50° E.; desc. 150 ft. over NE. slope.
- 16.95 Ravine, drains N. 80° E.; asc. 60 ft. over SE. slope.
- 19.80 Spur, slopes E.; desc. 155 ft. over NE. slope.
- 25.75 Creek, 4 lks. wide, course S. 30° E.; asc. 515 ft. over SE. slope.
- 37.25 Base of rock bluff, 60 ft. high, edge bears E. and W.
- 38.54 The 1/4 sec. cor. of sec. 5 only, perpetuated and recorded by Vernon R. Tracy, County Surveyor, in 1963, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 25 S
1/4 |
S 5 |
R 8 W
1963

from which the original bearing trees

A madrone, 15 ins. diam., bears S. 30° W., 34 lks. dist., with scribe marks 1/4 S5 BT visible on opened blaze.

A fir, 38 ins. diam., bears N. 50° W., 19 lks. dist., with healed blaze, and scribe marks 1/4 S5 CS BT visible on bark.

and a bearing tree mkd. by Tracy

A fir, 15 ins. diam., bears S 2° W., 58 lks. dist., with healed blaze.

N. 0° 06' W., beginning new measurement.

Ascend 60 ft. over SE. slope.

- 0.50 Enter logged area, edge bears E. and W.
 - 1.20 Spur, slopes S. 50° E.; desc. 70 ft. over NE. slope.
 - 3.14 Point for the 1/4 sec. cor. of sec. 4 only, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.