

County Surveyor's Record, Douglas County, Oregon

16456

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

T 25 S R 8 W
| 1/4
| S 4
1979

from which

A sawed fir stump, 12 ins. diam., bears N. 62 1/2° E.,
27 lks. dist., mkd. 1/4 S4 BT.

A sawed fir stump, 48 ins. diam., bears S. 26° E.,
37 lks. dist., mkd. 1/4 S4 BT.

Descend 25 ft. over NE. slope.

- 4.45 Ravine, drains E.; asc. 195 ft. over SE. slope.
- 10.45 Case Knife Ridge, bears S. 45° W. and E.; desc. 400 ft. over NW. slope, also enter timber, edge bears same as ridge.
- 22.40 Ravine, drains N. 60° W.; desc. 30-ft. over SW. slope.
- 24.25 Spur, slopes N. 60° W.; desc. 195 ft. over N. slope.
- 28.65 Creek, 1 lk. wide, course N. 65° W.; asc. 65 ft. over SW. slope.
- 32.45 Spur, slopes W.; desc. 365 ft. over NW. slope.
- 44.25 Case Knife Creek, 5 lks. wide, course N. 65° E.; asc. 105 ft. over SE. slope.
- 46.47 Intersect the S. bdy. of sec. 32, T. 24 S., R. 8 W.

True point for the closing cor. of secs. 4 and 5.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 24 S R 8 W
S 32
S 5 | S 4
C C
T 25 S R 8 W
1979

from which bearing trees mkd. by Henry R. Reppeto,
Registered Land Surveyor No. 618, in 1975

A fir, 40 ins. diam., bears S. 61 1/2° E.; 35 lks. dist., with scribe marks S4 BT visible on bark blaze.

A fir, 45 ins. diam., bears S. 67° W., 124 lks. dist., with scribe marks S5 BT visible on bark blaze.

From this point, a corner established and recorded by Henry R. Reppeto, Registered Land Surveyor No. 618, in 1975, bears S. 70° 30' E., 0.18 chs. dist., monumented with a brass tablet, 2 ins. diam., set in drill hole in exposed bedrock, mkd. NE S5.

From this same point, the original closing cor. of secs. 4 and 5, bears N. 0° 06' W., 0.17 chs. dist., determined from the remains of the original bearing trees: