

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

16457

CHAINS

A fir stump, 36 ins. diam., bears S. 9° E., 62 lks. dist., with scribe marks T25S R8 W S5 BT visible on opened blaze. (Record, S. 14° 50' E.)

A root hole, bears S. 62 1/2° W., 70 lks. dist., with a down fir alongside, 38 ins. diam., with scribe marks 25S R8W S4 visible on partially open blaze.

From this same point, the cor. of secs. 32 and 33 only, T. 24 S., R. 8 W., bears N. 89° 36' E., 2.92 chs. dist., hereinbefore described.

Land, mountainous.

Soil, rocky clay.

Timber, fir, yew, hemlock, maple, cedar, alder, dogwood, and chinquapin; undergrowth, Huckleberry, hazel, blackberry, arrowwood, willow, vine maple, Oregon grape, salal, fern, salmonberry, thimbleberry, and wild rose.

From the cor. of secs. 8 and 17 only.

N. 89° 51' W., bet. secs. 8 and 17.

Descend 50 ft. over SW. slope, through heavy timber and dense undergrowth.

1.05 Dirt road, 15 lks. wide., bears N. 10° W. and S. 10° E., also enter logged area, edge bears S. 15° E. and W.

6.75 Ravine, drains S.; asc. 65 ft. over SE. slope.

13.85 Spur, slopes S.; desc. 20 ft. along broken SW. slope.

17.50 Spur, slopes S.; desc. 770 ft. over SW. slope.

18.50 Enter timber, edge bears E. and S.

27.00 A corner established by person(s) unknown, monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground.

41.70 Creek, 2 lks. wide, course S. 20° W.; asc. 35 ft. over SE. slope.

42.75 Spur, slopes S. 20° W.; desc. 95 ft. over SW. slope.

45.25 From this point, a corner established by Henry R. Reppeto, Registered Land Surveyor No. 618, in 1975, for Weyerhaeuser Timber Co., bears South, 0.075 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd. 25S SW 1/4 S8 S17, from which the remains of bearing trees mkd. by Reppeto:

A fir snag, 42 ins. diam., bears N. 15 1/2° E., 42 lks. dist., with a nail with "W" embossed on head, at base.

A cedar, 32 ins. diam., bears N. 80° E., 92 lks. dist., with scribe marks T25S R8W S8 1/4 BT visible on open blaze.

A fir, 50 ins. diam., bears S. 15° E., 32 lks. dist., with scribe mars T25S R8W S17 1/4 BT visible on bark blaze.