

# County Surveyor's Record, Douglas County, Oregon

16458

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
47.99	<p>A fir snag, 50 ins. diam., bears N. 56 1/2° W., 34 lks. dist., with a nail with "W" embossed on head, at base.</p> <p>The 1/4 sec. cor. of secs. 8 and 17, determined at record distance from the remains of the original bearing trees:</p> <p style="padding-left: 40px;">An alder, 16 ins. diam., bears N. 53° W., 20 lks dist., with illegible scribe marks visible on opened blaze. (Record, N. 30° W.)</p> <p style="padding-left: 40px;">An alder snag, 14 ins. diam., bears S. 57 1/2° W., 35 lks. dist., with illegible scribe marks visible on opened blaze. (Record, S. 75° W.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 25 S R 8 W</p> <p style="margin-left: 100px;">S 8</p> <p style="margin-left: 80px;">1/4 S 17</p> <p style="margin-left: 100px;">1979</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears N. 49 1/2° W., 36 lks. dist., mkd. 1/4 S8 BT.</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 56 1/2° W., 6 1/2 lks. dist., mkd. 1/4 S17 BT.</p> <p>Corner is located 1.50 chs. N. of gravelled road, 25 lks. wide, bears N. 45° W. and S. 45° E.</p> <p>Land, mountainous. Soil, rocky clay. Timber, yew, cedar, fir, hemlock, maple, alder, dogwood and chinquapin; undergrowth, blackberry, huckleberry, salal, Oregon grape, vine maple, rhododendron; fern, manzanita, hazel, arrowwood, wild rose, and young timber.</p>
16.45	<p>From the cor. of secs. 5 and 8 only.</p> <p>N. 89° 30' W., bet. secs. 5 and 8.</p> <p>Ascend 520 ft. over NE. slope, through moderate timber and dense and undergrowth.</p> <p>Ridge, bears N. 20° W. and S. 20° E.; desc. 365 ft. over general W. slope.</p>
18.50	<p>Dirt road, 15 lks. wide, bears N. 60° W. and S., in curve.</p>
23.74	<p>A corner established by Henry R. Reppeto, Registered Land Surveyor, No. 618, in 1975, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with pipe cap mkd. E 1/16 S5, from which bearing trees mkd. by Reppeto:</p> <p style="padding-left: 40px;">A fir, 62 ins. diam., bears N. 31 3/4° E., 23 lks. dist., with scribe marks E 1/16 S5 BT visible on open blaze.</p>