

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

16459

CHAINS

A fir, 24 ins. diam., bears S. 49° E., 41 lks. dist., with a nail with "W" embossed on head, at base.

Descend 130 ft. over general W. slope.

26.57 Point for the E 1/16 sec. cor. of secs. 5 and 8.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in drill hole, in exposed bedrock, with top mkd.

E 1/16 $\frac{S\ 5}{S\ 8}$
1977

from which

A cedar, 10 ins. diam., bears N. 85 3/4° E., 50 lks. dist., mkd. E 1/16 S5 BT.

A fir, 31 ins. diam., bears S. 4° W., 56 lks. dist., mkd. E 1/16 S8 BT.

Descend 130 ft. over general W. slope.

31.55 Dry creek bed, 1 lk. wide, drains N. 70° W.; desc. 10 ft. over NE. slope.

36.05 Top of ascent, slopes NW.: desc. 40 ft. over general W. slope.

47.45 The 1/4 sec. cor. of secs. 5 and 8, perpetuated by person(s) unknown, monumented with an iron pipe, 1 in. diam., firmly set, projecting 18 ins. above ground, from which the remains of the original bearing trees:

A cedar, 18 ins. diam., bears N. 20° W., 41 lks. dist., with scribe marks 1/4 S5 BT visible on open blaze. (Record, 32 lks.)

A cedar, 50 ins. diam., bears S. 60° E., 17 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd.

T 25 S R 8 W
1/4 $\frac{S\ 5}{S\ 8}$
1977

Reset iron pipe alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, alder, maple, madrone, and oak; undergrowth, vine maple, hazel, arrowwood, huckleberry, salal, Oregon grape, blackberry, and fern.

From the 1/4 sec. cor. of secs. 5 and 6, perpetuated and recorded by Donald L. Peel, Registered Land Surveyor, No 752, in 1967, for Weyerhaeuser Timber Co., monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 4 ins. above ground, from which an original bearing tree: