

County Surveyor's Record, Douglas County, Oregon

16460

Dependent Resurvey, Poriton of Subdivisional Lines,
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 15 ins. diam., bears N. 50 1/4° E., 10 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.
in the ground, directly over iron pipe, with brass cap
mkd.

T 25 S R 8 W
1/4
S 6 1/2 S 5
1979

from which a new bearing tree

A fir, 8 ins. diam., bears N. 58 1/2° W., 13 1/2 lks.
dist., mkd. 1/4 S6 BT.

N. 0° 17' E., bet. secs. 5 and 6.

Descend 300 ft. over NW. slope, along W. edge of logged
area.

17.55 Creek, 3 lks. wide, course W.; asc. 360 ft. over S.
slope.

35.90 Spur, slopes W.; desc. 85 ft. over NW. slope.

46.92 Intersect the S. bdy. of sec. 31, T. 24 S., R. 8 W.

True point for the closing cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 24 S R 8 W
S 31
9 6 1/2 S 5
T 25 S R 8 W
C C
1979

from which

A maple, 9 ins. diam., bears S. 60 1/2° E., 38 lks.
dist., mkd. T25S R8W S5 CC BT.

A cedar, 48 ins. diam., bears S. 3° W., 68 lks.
dist., mkd. T25S R8W S6 CC BT.

From this point, the original closing cor. of secs. 5 and
6, bears N. 0° 17' W., 0.042 chs. dist., perpetuated and
recorded by Donald L. Peel, Registered Land Surveyor, No.
752, in 1967, for Weyerhaeuser Timber Co., monumented
with an iron pipe, 1/2 in. diam., firmly set, projecting 12
ins. above ground, from which the remains of the original
bearing trees:

A sawed cedar stump, 48 ins. diam., bears S. 46 1/2° E.,
40 lks. dist., no marks visible.

A sawed maple stump, 30 ins. diam., bears S. 19 1/2° W.,
22 lks. dist., with open blaze, no marks visible.

From this same point, the cor. of secs. 31 and 32 only,
T. 24 S., R. 8 W., bears N. 89° 52' E., 3.48 chs. dist.,
hereinbefore described.