

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 25 S., R. 8 W., Willamette Meridian, Oregon

16461

CHAINS

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, cedar, maple, yew, dogwood, and madrone;  
undergrowth, fern, salal, arrowwood, vine maple, Oregon  
grape, blackberry, hazel, and young timber.

The point for the 1/4 sec. cor. of sec. 5 only, is at proportionate distances on the N. bdy. of sec. 5.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 8 W

1/4 S 5

T 25 S R 8 W  
1979

from which

A hemlock, 10 ins. diam., bears S. 11° E., 60  
lks. dist., mkd. 1/4 S5 BT.

A fir, 18 ins. diam., bears S. 21° W., 20 1/2 lks.  
dist., mkd. 1/4 S5 BT.

From this point, the 1/4 sec. cor. of sec. 32 only,  
T. 24 S., R 8 W., bears N. 89° 38' E., 5.67 chs. dist.,  
hereinbefore described.

The point for the E 1/16 sec. cor. of sec. 5 only, is at proportionate distance on the N. bdy. of sec. 5.

Seat a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in  
drill hole, in exposed sandstone bedrock, with top mkd.

E 1/16 S 5  
1979

from which

A hemlock, 23 ins. diam., bears S. 15° E., 49 lks.  
dist., mkd. E 1/16 S5 BT.

A hemlock, 10 ins. diam., bears S. 72 3/4° W., 48 lks.  
dist., mkd. E 1/16 S5 BT.

From this point, the 1/4 sec. cor. of sec. 32 only,  
T. 24 S., R. 8 W., bears N. 89° 36' W., 13.79 chs. dist.,  
hereinbefore described.

The point for the 1/4 sec. cor. of sec. 6 only, is at proportionate distance on the N. bdy. of sec. 6.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 8 W

1/4 S 6

T 25 S R 8 W  
1979

from which