

# County Surveyor's Record, Douglas County, Oregon

16462

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 25 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>A hemlock, 20 ins. diam., bears S. 2 1/2° W., 39 lks. dist., mkd. 1/4 S6 BT.</p> <p>A cedar, 43 ins. diam., bears S. 63 3/4° W., 17 lks. dist., mkd. 1/4 S6 BT.</p> <p>From this point, the 1/4 sec. cor. of sec. 31 only, T. 24 S., R. 8 W., bears S. 89° 48' E., 3.96 chs. dist., hereinbefore described.</p>
	<p>Subdivision of Section 5, T. 25 S., R 8 W., Willamette Meridian, Oregon</p>
	<p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N. 1° 48' E., on the N. and S. center line of sec. 5.</p> <p>Descend 40 ft. over NE. slope, through heavy timber and dense undergrowth.</p>
0.65	Creek, 5 lks. wide, course N. 35° W.; asc. 5 ft. over SW. slope.
2.80	Spur, slopes N. 50° W.; desc. 60 ft. over NW. slope.
9.40	Creek, 15 lks. wide, course S. 65° W.; asc. 495 ft. over SW. slope.
22.75	Gravelled road, 25 lks. wide, bears N. 60° E. and S. 60° W.
29.00	Spur slopes S. 40° E.; asc. 255 ft. over SE. slope.
40.36	Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line.
	<p>Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 S R 8 W C 1/4 S 5 1979</p>
	<p>from which</p> <p>A fir, 13 ins. diam., bears N. 55 1/2° E., 12 1/2 lks. dist., mkd. C 1/4 S5 BT.</p> <p>A fir, 20 ins. diam., bears S. 30 1/2° W., 48 lks. dist., mkd. C 1/4 S5 BT.</p>
	Ascend 240 ft. over SE. slope.
50.60	Spur, slopes W.; desc. 430 ft. over NW. slope.
51.70	Dirt road, 15 lks. wide, bears E. and W.
61.35	Gravelled road, 25 lks. wide, bears N. 50° W. and S. 50° E.
63.10	Creek, 4 lks. wide, course N. 70° W.; asc. 205 ft. over SW. slope.
68.60	Spur, slopes W.; asc. 40 ft. over SW. slope.