

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 5, T. 25 S., R. 8 W.,  
Willamette Meridian, Oregon

16463

**CHAINS**

- 74.05 Spur, slopes N. 75° W.; desc. 105 ft. over NW. slope.
- 78.65 Ravine, drains S. 80° W.; asc. 10 ft. over SW. slope.
- 87.10 The 1/4 sec. cor. of sec. 5 only, on the N. bdy. of the Tp.

From the 1/4 sec. cor. of sec. 5 only, on the E. bdy. of the sec.

S. 89° 21' W., on the E. and W. center line of sec. 5.

Descend 100 ft. over SW. slope, through heavy timber and dense undergrowth.

- 7.65 Head of ravine, drains S. 20° E.; asc. 420 ft. over SE. slope.
- 14.10 Ridge, bears N. 45° W. and S. 45° E.; desc. 65 ft. over SW. slope.
- 18.50 Head of ravine, drains S.; asc. 40 ft. over SE. slope.
- 22.14 A corner established by Henry R. Reppeto, Registered Land Surveyor, No. 618, in 1975, monumented with an iron post 2 ins. diam., firmly set, projecting 8 ins. above ground, with cap mkd.

CE 1/16  
S 5

from which a bearing tree mkd. by Reppeto

A fir, 40 ins. diam., bears N. 65° E., 32 lks.  
dist., with scribe marks CE 1/16 S5 BT visible  
on bark blaze.

- 22.20 Enter logged are, edge bears N. and S.
- 23.90 Spur, slopes S.; desc. 5 ft. over SW. slope.
- 25.40 Point for the center E. 1/16 sec. cor. of sec. 5.  
  
Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

C  $\frac{E\ 1/16}{S\ 5}$  C  
1979

from which

A sawed fir stump, 24 ins. diam., bears N. 39° E.,  
70 lks. dist., mkd. CE 1/16 S5 BT.

A sawed fir stump, 34 ins. diam., bears S. 15° E.,  
18 lks. dist., mkd. CE 1/16 S5 BT.

Descend 165 ft. over SW. slope.

- 28.90 Dirt road, 20 lks. wide, bears N. 30° W. and S. 30° E.
- 31.25 Enter timber, edge bears N. 70° W. and S. 70° E.
- 33.00 Spur, slopes S. 20° W.; desc. 180 ft. over SW. slope.
- 36.85 Ravine, drains S. 55° W.; desc. 20 ft. over SW. slope.