

County Surveyor's Record, Douglas County, Oregon

16464

Subdivision of Section 5, T. 25 S., R. 8 W.,
Willamette Meridian, Oregon

CHAINS	
37.30	Ravine, drains S.; asc. 80 ft. over SE. slope.
40.05	Spur, slopes S.; desc. 25 ft. over SW. slope.
42.80	Ravine, drains S. 20° E.; asc. 110 ft. over SE. slope.
44.32	A corner established by Henry R. Reppeto. Registered Land Surveyor No. 618, in 1975, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, from which bearing trees mkd. by Reppeto: <div style="margin-left: 40px;">A fir, 34 ins. diam., bears N. 2° E., 73 lks. dist., with a nail with "W" embossed on head, at base.</div> <div style="margin-left: 40px;">A fir, 27 ins. diam., bears S. 41° W., 53 lks. dist., with a nail with "W" embossed on head, at base.</div>
45.47	The center 1/4 sec. cor. of sec. 5. Ascend 45 ft. over SE. slope.
46.75	Spur, slopes S. 20° W.; desc. 160 ft. over SW. slope.
53.00	Ravine, drains S. 25° W.; asc. 50 ft. over SE. slope.
57.40	Spur, slopes S. 50° W.; desc. 575 ft. over NW. slope.
66.95	Gravelled road, 25 lks. wide, bears N. and S.
74.75	Enter logged area, edge bears N. and W.
75.10	Gravelled road, 20 lks. wide, bears N. 30° W. and S. 30° E.
83.19	The 1/4 sec. cor. of secs. 5 and 6.
	From the center E 1/16 sec. cor. of sec. 5. N. 1° 00' E., on the N. and S. center line of the NE 1/4 of sec. 5. Ascend 150 ft. over SW. slope, through logged area.
8.50	Ridge, bears N. 40° W. and E.; desc. 360 ft. over NE. slope.
23.85	Spur, slopes N. 40° E.; desc. 200 ft. over NW. slope.
29.75	Creek, 1 lk. wide, course N. 35° E.; desc. 175 ft. along E. slope.
33.70	Spur, slopes N. 20° E.; desc. 105 ft. over NW. slope.
39.70	Ravine, drains N. 80° E.; asc. 90 ft. over SE. slope.
43.20	Spur, slopes S. 80° E.; desc. 85 ft. over NE. slope.
46.50	Creek, 1 lk. wide, course E.; asc. 5 ft. over SE. slope.
46.64	The E 1/16 sec. cor. of sec. 5 only, on the N. bdy. of the Tp.
	From the E 1/16 sec. cor. of secs. 5 and 8.