

# County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey of a Portion of  
the Subdivisional Lines,  
T. 27 S., R. 1 W., Willamette Meridian, Oregon

16468

**CHAINS**

From the cor. of secs. 17, 18, 19, and 20, perpetuated and recorded by Thomas E. Shrum, Jr., Registered Engineer No. 4287, in 1961, and further perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1969, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 27 S R 1 W

S 18 | S 17

S 19 | S 20

BLM 1971

1969

FD OK

K. Hoffine 7/95

M122-27

from which bearing trees marked by Shrum:

A cedar, 50 ins. diam., bears N. 45° E., 318 lks. dist., with scribe marks 27S R1W S17 BT visible on partially healed blaze.

A cedar stump, 28 ins. diam., bears S. 89° E., 235 lks. dist., with scribe marks T27S R1W S20 R 4287 visible on open blaze.

and bearing trees mkd. by Powell

A fir, 13 ins. diam., bears S. 81° E., 47 lks. dist., with healed double blaze.

A fir, 10 ins. diam., bears N. 32° W., 41 lks. dist., with healed double blaze.

and a bearing tree of which I have no record

A fir, 8 ins. diam., bears S. 58° W., 40 lks. dist., with scribe marks T27S R1W BT visible on open blaze.

West, bet. secs. 18 and 19, marking and blazing the true line.

Descend 230 ft. over W. slope, through heavy timber and dense undergrowth.

- 7.25 Gravelled road, 20 lks. wide, bears N. 20° E. and S. 20° W.
- 14.60 Ravine, drains N.; asc. 60 ft. over NE. slope.
- 18.20 Spur, slopes N.; desc. 200 ft. over NW. slope.
- 29.20 White Creek, 3 lks. wide, course N. 5° E.; asc. 140 ft. over NE. slope.
- 39.64 The 1/4 sec. cor. of secs. 18 and 19, perpetuated and recorded by Ronald A. Quimby Registered Land Surveyor No. 1654, in 1980, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 27 S

1/4 S 18

S 19

R 1 W

1980 RLS 1654

from which the remains of the original bearing trees