

County Surveyor's Record, Douglas County, Oregon

16472

T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, township 27 south, range 3 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey, is as follows:

A portion of the subdivisional lines was surveyed by Samuel C. Flint, in 1882.

A portion of the subdivisional lines was resurveyed by Harold D. Corbin, in 1958.

The resurvey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated September 10, 1979, under Group Number 995, Oregon.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retrace-ment data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. All lines not forming a closure were measured twice.

The geographic position of the corner of sections 22, 23, 26, and 27, as scaled from the Dixonville, Oregon, quadrangle map, published by the United States Geological Survey, in 1954, is as follows:

Latitude 43° 11.9' N. Longitude 123° 01.8' W.

The mean magnetic declination is 18° 30' E.

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 27 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the survey by Samuel C. Flint,
U. S. Deputy Surveyor, in 1882)

Beginning at the cor. of secs. 22, 23, 26, and 27, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1957, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

FD OK
H. Heimbarger
11/96 4126-11

COUNTY SURVEYORS OFFICE

S 22 | S 23
S 27 | S 26
1957

PER BLM LETTER
DATED 2/13/84 - BEN
SHOULD BE 1947 - BEN
B. IRVING SET CAP.
T.R.

from which the remaining original bearing tree, remarked by Byron

A fir, 44 ins. diam., bears N. 27 1/2° W., 50 lks. dist., with original fragmentary scribe marks visible on bark blaze and scribe marks T27S R3W S22 CS BT visible on bark blaze. (Record, N. 23° W.)