

# County Surveyor's Record, Douglas County, Oregon

16473

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

and the remains of bearing trees mkd. by Byron

A fir snag, 18 ins. diam., bears N. 70° E., 73 1/2 lks. dist., with fragmentary scribe marks visible on open blaze.

A fir snag, 20 ins. diam., bears S. 74° E., 54 1/2 lks. dist., with fragmentary scribe marks visible on open blaze.

and new bearing trees

An oak, 10 ins. diam., bears N. 71° E., 12 1/2 lks. dist., mkd. T27S R3W S23 BT.

An oak, 10 ins. diam., bears S. 74 3/4° E., 6 1/2 lks. dist., mkd. T27S R3W S26 BT.

An oak, 8 ins. diam., bears S. 41 3/4° W., 69 lks. dist., mkd. T27S R3W S27 BT.

An oak, 13 ins. diam., bears N. 34 1/4° W., 28 lks. dist., mkd. T27S R3W S22 BT.

S. 87° 16' W., bet. secs. 22 and 27, marking and blazing the true line.

Ascend 180 ft. over SE. slope. through scattering timber and dense undergrowth.

17.70 Top of ascent, slopes S.; desc. 25 ft. over SW. slope.

20.155 A corner established and recorded by Thomas E. Shrum, Jr., Registered Professional Engineer No. 4287, in 1978, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with aluminum cap mkd.

T 27 S R 3 W  
S 22  
S 27 E 1/16

Bottom of descent, slopes S.; asc. 30 ft. over SE. slope.

40.15 The 1/4 sec. cor. of secs. 22 and 27, reestablished by proportionate measurement and recorded by Thomas E. Shrum Jr., Registered Professional Engineer No. 4287, in 1978, and is accepted as the best available evidence of the position of the original corner, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd.

FDOK  
M. Heimbarger  
11 1976  
M126-11

T 27 S R 3 W  
S 22  
S 27 1/4

from which

A fir, 5 ins. diam., bears N. 22° E., 12 lks. dist., mkd. 1/4 S22 BT.

A fir, 5 ins. diam., bears S. 59° W., 18 lks. dist., mkd. 1/4 S27 BT.

S. 87° 16' W., beginning new measurement.

Ascend 155 ft. over SE. slope.