

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 27 S., R. 3 W., Willamette Meridian, Oregon

16474

CHAINS

20.01 The W 1/16 sec. cor. of secs. 22 and 27, established and recorded by Thomas E. Shrum Jr., Registered Professional Engineer No. 4287, in 1978, and is accepted as the corner, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd.

T 27 S R 3 W
S 22
S 27 W 1/16

from which

A fir, 10 ins. diam., bears N. 3° E., 15 lks. dist., mkd. W 1/16 S22 BT.

A fir, 19 ins. diam., bears S. 48 1/2° W., 45 lks. dist., mkd. W 1/16 S27 BT.

S. 87° 16' W., beginning new measurement.

Ascend 365 ft. over SE. slope.

20.01 The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

T 27 S R 3 W
S 21 | S 22
S 28 | S 27
1958

from which the remains of the original bearing trees

A root hole, bears N. 47 1/2° E., 52 lks. dist., with a down fir alongside, 42 ins. diam., no marks visible.

A madrone, 33 ins. diam., bears S. 54° E., 115 lks. dist., no marks visible on open blaze. (Record, 113 lks.)

A fir, 35 ins. diam., bears N. 10° W., 37 lks. dist., with healed blaze.

and the remains of bearing trees mkd. by James W. Byron Deputy County Surveyor, in 1957

A cedar, 15 ins. diam., bears N. 68 1/2° E., 91 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A cedar, 13 ins. diam., bears S. 15° E., 74 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A root hole, bears S. 75° W., 7 1/2 lks. dist., with a down fir alongside, 38 ins. diam., no marks visible.

A pine, 23 ins. diam., bears N. 27 1/2° W., 21 1/2 lks. dist., with healed blaze.

and bearing trees mkd. by Corbin

A chinquapin, 12 ins. diam., bears N. 40° E., 108 lks. dist., with healed blaze.