

# County Surveyor's Record, Douglas County, Oregon

16475

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 27 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

A chinquapin, 9 ins. diam., bears S. 22 1/2° E., 26 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A chinquapin, 10 ins. diam., bears S. 52° W., 35 lks. dist., with fragmentary scribe marks visible on open blaze.

A fir, 8 ins. diam., bears N. 14 3/4° W., 46 lks. dist., with healed blaze.

Corner is located on top of ridge, bears NE. and SW.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, madrone, alder, chinquapin, and pine; undergrowth, salal, rhododendron, vine maple, poison oak, Oregon Grape, and fern.

N. 0° 20' W., bet secs. 21 and 22.

Over nearly level land on ridge top, through heavy timber and dense undergrowth.

2.80 Slopes changes to NE.; desc. 310 ft. over broken NE. slope.

10.15 Ravine, drains N. 80° E.; desc. 240 ft. over NE. slope.

19.705 Point for the S 1/16 sec. cor. of secs. 21 and 22.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16  
S 21|S 22  
1979

from which

A hemlock, 29 ins. diam., bears S. 86° E., 12 lks. dist., mkd. S 1/16 S22 BT.

A hemlock, 8 ins. diam., bears N. 38° W., 44 lks. dist., mkd. S 1/16 S 21 BT.

Descend 30 ft. over NE. slope

20.50 Enter logged area, edge bears N. 10° W. and E.

21.10 Ravine, drains N. 50° W.; desc. 130 ft. over NW. slope.

29.00 Creek, 10 lks. wide, course N. 75° E.; asc. 395 ft. over SE. slope.

39.41 The 1/4 sec. cor. of secs. 21 and 22, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1957, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 27 S  
S 21|S 22  
R 3 W  
1957

from which the remains of an original bearing tree