

County Surveyor's Record, Douglas County, Oregon

16483

T. 24 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, township 24 south, range 6 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey, is as follows:

A portion of the subdivisional lines was surveyed by Robert Elder and Henry S. Gile, in 1853.

A portion of the subdivisional lines was surveyed by Williams R. Whipple, in 1891.

A portion of the subdivisional lines was resurveyed and section 19 was subdivided by Joseph S. Gawron, in 1962.

A portion of the subdivisional lines was resurveyed by Daniel L. Berry and Charles E. Akin Jr., in 1973-1974.

The resurvey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated January 22, 1979, under Group Number 969, Oregon.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original survey was retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming closures were measured twice. Only those lines bounding or crossing public lands were blazed.

The geographic position of the corner of sections 26, 27, 34, and 35, as scaled from the Sutherlin, Oregon, quadrangle map, published by the United States Geological Survey, in 1954, is as follows:

Latitude $43^{\circ} 26.8' N$. Longitude $123^{\circ} 23.1' W$.

The mean magnetic declination is $19^{\circ} 30' E$.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon.

(Restoring the survey by Robert Elder and Henry S. Gile,
U. S. Deputy Surveyors, in 1853, and
the survey by Williams R. Whipple,
U. S. Deputy Surveyor, in 1891)

Beginning at the cor. of secs. 26, 27, 34, and 35, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1969, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.